



**SKIN & PONTOON
INTERNAL FLOATING ROOF
INPUT DATA SHEET**

Move to a higher standardSM

TANK INFORMATION REQUIRED

Tank Owner: _____ Location: _____ Date: _____

Tank Number: _____ Tank Ø: _____ ft Tank Height: _____ ft

Product Stored: _____ Stored Product Temperature: _____ °F

Design S.G.: 0.7 (default) Inlet Flow Rate: _____ Bbl/hr Inlet Nozzle Dia.: _____ in

Outlet Flow Rate: _____ Bbl/hr Tank Shell Design: Unknown

			QTY	
Center Column Diameter:	in			
1 st Ring Roof Column Diameter:	in	Radius: _____ in		
2 nd Ring Roof Column Diameter:	in	Radius: _____ in		
3 rd Ring Roof Column Diameter:	in	Radius: _____ in		Distance Between Poles
Gauge Pole Diameter:	in	Radius: _____ in		_____ in
Gauge Pole Diameter:	in	Radius: _____ in		_____ in
Gauge Pole Diameter:	in	Radius: _____ in		_____ in
Gauge Pole Diameter:	in	Radius: _____ in		_____ in

PLEASE SELECT SEAL TYPE

Primary Seal Type: None

Primary Seal Material: 304 Stainless Steel

Primary Fabric Material: Teflon (10mil)

Secondary Seal Type: None

Secondary Seal Material: 304 Stainless Steel

Secondary Fabric Material: Teflon (10mil)

Wiper Seal Type: None

Wiper Material: Polyethylene

PLEASE SELECT FOAM DAM TYPE

Foam Dam Options: _____

ADDITIONAL SEAL OPTIONS

Wax Scraper Fabric Supports

Shoe Shunts

TANK ACCESSORIES / INFO.

Radar Gauging

Vertical Ladder Fitted (roof-to-roof)

Tank Roundness / Tilt Report

Floating Suction Line

N2 Blanketed

REQUIRED IFR APPURTENANCE(S)

Suspended IFR Ladder Pad

Dip Funnel Rim Vent

Airscoops Pigging Vent

Float Well Manways(s)

COMMENTS

*PLEASE PROVIDE PLAN OF TANK NOZZLES & INTERNAL PIPING